SURGICAL APPARATUS FOR SUBSTITUTION WITH ARTIFICIAL JOINT

Publication number: JP5123334 (A)

Publication date: 1993-05-21

Inventor(s): YAGI WATARU; YAWADA MASUO: ISHII MASAMI; SAWAI KAZUHIKO; OTSUKA HIRCRIT, YAMAMOTO TAKAHIRO; MATSUDA YASUMASA: HATTORI YUICHI

Applicant(a): AISIN SERU

Classifications

- international: A61817/16; A61817/56; A61F2/30; A61817/17; A61B17/16; A61B17/56; A61F2/30;

(PC1-7): A61817/16. A61817/58. A61F2/30

A61817/1652C

Application number: JP1991029175G 19911107

Priority number(s): JP19910291756 19911107

Abstract of JP 5123334 (A)

PURPOSE To provide a surgical operation apparatus, which does not require skillfulness of the operator, can shorten the time for operation, and prevent eccentric wear and joint dislocation caused by misinstaliation of a sooket. CONSTITUTION An operation apparatus for substitution with an artificial joint comprises a supporting rod 1, a gripping part 2 mounted on the rod 1, a socket interlocked shalt 3b working stidably within the rod 1, a socket chuck part 3 secured to the sockel interlooked shaft 3b, and a lever 4 interloked with the sockot interlocked shalt 3b, wherein a socket 50 is mounted in and removed from the socket chuck part 3 by turning the lever 4. The supporting shaft t is furnished with an angle. indicator 20 having an angle Indicator with an angle indicator rod 9 which can make setting of specified angle relative to the supporting shaft 1.

